

Extractores Eólicos Soluciones de Ventilación

Extractor Eólico Residencial | Tamaño 8 - 12 - 14

Datos del Producto





the internally and externally braced turbines both have the same internal construction, the externally braced turbines have three braces that surround the outside of the turbine.

Features — All Whirlybird turbines come with a Lifetime Transferable Warranty. Simply put, you can't buy a better turbine. The turbine design features permanently

Lifetime Transferable Warranty. Simply put, you can't buy a better turbine. The turbine design features permanently lubricated upper and lower ball bearings that ensure long life and no maintenance. Other common features of the turbine are its rigid spider-type construction — riveted at every connection and tested to withstand winds of 110 M.P.H., 21 air-foil curved vanes with rolled edges to deflect water, and 100% rust-free all-aluminum construction.

Installation — The Whirlybird turbine's large flashing makes installation easy. The Whirlybird turbine's exclusive vari-pitch base adjusts to a 12/12 roof pitch for use on many roof applications. When installed properly, the Whirlybird turbine reduces energy bills and the likelihood of winter ice buildup.











Product Listings

Model	MD	TDI
BIB-12	•	•
BEB-12	•	•
BIB-12TR	•	•
BEB-12TR	•	•
BIB-14	•	•
BEB-14	•	•



The	Whirlybird
34	All-Weather Turbine Vent

Model	Hole Size	Height	Base	Ctn. Qty.	Ctn. Wt. (lbs)
BIB-12	12"	171⁄4"	20" x 20"	1	61/2
BEB-12	12"	175/8"	20" x 20"	1	6¾
BIB-12TR	12"	201/4"	20" x 20"	1	6¾
BEB-12TR	12"	20%"	20" x 20"	1	6¾
BIB-14	14"	20"	22" x 22"	1	71/2
BEB-14	14"	20%"	22" x 22"	1	7¾
TIB-12 (Head)	_	111⁄4"	_	1	41/2
TEB-12 (Head)	_	11%"	_	1	43/4
TIB-14 (Head)	_	11%"	_	1	43/4
TEB-14 (Head)	_	12"	_	1	5
GT-12 Galvanized Steel	12"	15¾"	20" x 20"	1	9
GEB-12 Galvanized Steel	12"	16"	20" x 20"	1	9½
IB-8 (Head)	8"	141⁄4"	_	1	4
VP-8 (Base)	8"	7¾"	16" x 16"	1	21/4
HCAP12	_	_	_	25	16¾
HCAP14	_	_	_	25	20

BIB-12



BEB-12





BIB-14

BEB-14



- Forever guarantee residential use only.
- All-aluminum construction.
- Exclusive vari-pitch base adjusts to 12/12 roof pitch.
- Tested to withstand winds of 110 M.P.H.
- Easy installation.

General Specifications for Turbines

- BIB & TIB are internally braced.
- BEB & TEB are **externally** braced.
- GT-12, GEB-12, & IB-8 available in mill finish only.
- Model number denotes throat size.
- TR turbines are for tile roof applications.
- **B** Series are packaged with base.
- **T** Series are packaged without base.



Permanently lubricated upper and lower ball bearings that ensure long life and no maintenance.



Tile Whirlybird® Turbine Vents

BIB12TR



BEB12TR



- Approved for all tile and slate roof construction.
- BIB12TR is an internally braced 12" turbine.
- BEB12TR is an externally braced 12" turbine.
- Vari-pitch base adjust to a 12/12 roof pitch.

Galvanized Turbine Vents





- 0.015 stamped galvanized steel.
- Fits any roof pitch to 7/12.
- GT-12 is an internally braced 12" turbine.
- GEB-12 is an externally braced 12" turbine.
- Residential or light commercial use only.

Vent Selector Guide

Select the Attic Floor Space to be ventilated and an Exhaust System — find where the two intersect to determine the amount of exhaust vents needed. Select an Intake System and repeat the steps to determine the amount of intake vents needed.

ATTIC FLOOR SPACE IN SQ FT:	1000	1500	2000	2500	3000	3500
	Intake	Intake	Intake	Intake	Intake	Intake
EXHAUST SYSTEM	C416 C616 C816 C816 105/190 140 SV-10 DA-4/IV-9	C416 C616 C816 C816 105/190 140 SV-10 DA-4/IV-9	C416 C416 C616 C816 105/190 140 SV-10 DA-4/IV-9	C416 C416 C616 C816 105/190 140 SV-10 DA-4/IV-9	Exhaust C416 C616 C816 105/190 140 SV-10 DA-4/IV-9	Exhaust C416 C616 C616 C816 105/190 140 SV-10 DA-4/IV-9

Turbines

12" Turbines	2	21	15	8	8	6	9	15	2 2	1 15	8	8	6	9	15	3	32	22	12	11	9	13	22	4	42	29	16	15	12	17 2	29	4	42	29	16	15	12	17	29	5	52	2 36	5 20	18	8 1	5 2	1 3	6
14" Turbines	1	14	10	6	5	4	6	10	2 28	3 19	11	10	8	11	20	2	28	19	11	10	8	11	20	3	42	29	16	15	12	17 2	29	3	42	29	16	15	12	17	29	4	56	6 38	3 22	2 20	0 1	6 2	2 3	9

